



Open Cavity Plastic Packages Availability List

Updated July 2007

Open -Pak QFN/MLP/DFN Package Configuration Options (Dimensions in Millimeters)

Body Size	Lead Count	Die Pad Size	Lead Pitch	Body Thickness
3x3	10	1.36X2.20	.50	.75
3X3	12	1.36 SQ	.65	.75
3X3	16	1.36 SQ	.50	.75
4X4	12	2.30 SQ	.80	.80
4X4	16	2.30 SQ	.65	.80
4X4	20	2.30 SQ	.50	.80
4X4	24	2.30 SQ	.50	.80
5X5	16	3.10 SQ	.80	.80
5X5	20	3.30 SQ	.65	.80
5X5	24	3.10 SQ	.65	.80
5X5	28	3.10 SQ	.50	.80
5X5	32	3.30 SQ	.50	.80
6X6	24	4.24 SQ	.65	.80
6X6	28	4.24 SQ	.65	.80
6X6	36	4.24 SQ	.50	.80
6X6	40	4.24 SQ	.50	.80
7X7	28	5.20 SQ	.80	.80
7X7	32	5.20 SQ	.65	.80
7X7	44	5.20 SQ	.50	.80
7X7	48	5.20 SQ	.50	.80
8X8	28	6.00 SQ	.80	.80
8X8	32	6.00 SQ	.80	.80
8X8	52	6.00 SQ	.50	.80
8X8	56	6.00 SQ	.50	.80
9X9	64	6.90 SQ	.50	.80
12X12	80	9.00 SQ	.50	.80

Open-Pak TQFP/LQFP Package Configuration Options (Dimensions in Millimeters)

Body Size	Lead Count	Die Pad Size	Lead Pitch	Body Thickness
10X10	44	6.86 SQ	.80	1.14
10X10	52	6.86 SQ	.65	1.14
10X10	64	6.86 SQ	.50	1.14

**Open-Pak SOIC Package Configuration Options
(Dimensions in Inches)**

Body Width	Lead Count	Die Pad Size	Lead Pitch	Body Thickness
.150	8	.075X.100	.050	.055
.150	14	.075X.100	.050	.055
.150	16	.075X.120	.050	.055
.300	16	.150X.220	.050	.093
.300	20	.150X.220	.050	.093
.300	24	.150X.220	.050	.093
.300	28	.160X.230	.050	.093

Open-Pak SSOP Package Configuration Options

Body Width	Lead Count	Die Pad Size	Lead Pitch	Body Thickness
.150	16	.070X.100	.025	.055

**Open -Pak SOIC HEAT ENHANCED Package Configuration Options
(Dimensions in Inches)**

Body Width	Lead Count	Die Pad Size	Lead Pitch	Body Thickness
.150	8	.075X.100	.050	.055
.150	14	.075X.100	.050	.055
.150	16	.075X.120	.050	.055
.300	16	.150X.220	.050	.093
.300	20	.150X.220	.050	.093
.300	24	.150X.220	.050	.093
.300	28	.160X.230	.050	.093

**Open-Pak SSOP HEAT ENHANCED Package Configuration Options
(Dimensions in Inches)**

Body Width	Lead Count	Die Pad Size	Lead Pitch	Body Thickness
.150	16	.070X.100	.025	.055